

MULTI-SPLIT AMSD-A SERIES WITH WALL MOUNTED-R22

HEAT PUMP MODEL		OUTDOOR UNIT		AMSD1010AR		AMSD1015AR		AMSD1515AR			
		INDOOR UNIT		2 x AWM010GR		AWM010GR		AWM015GR			
NOMINAL COOLING CAPACITY		Btu/h		2 x 9100		9100		11500			
		W		2 x 2670		2670		3370			
NOMINAL HEATING CAPACITY		Btu/h		2 x 10700		10700		12000			
		W		2 x 3140		3140		3520			
COOLING ONLY MODEL		OUTDOOR UNIT		AMSD1010A		AMSD1015A		AMSD1515A			
		INDOOR UNIT		2 x AWM010G		AWM010G		AWM015G			
NOMINAL CAPACITY		Btu/h		2 x 9500		9500		12700			
		W		2 x 2780		2780		3720			
POWER SOURCE		V/Ph/Hz		220 ~ 240 / 1 / 50				220 ~ 240 / 1 / 50			
INDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	260 / 10.2				260 / 10.2			
		WIDTH	mm/in	899 / 35.4				899 / 35.4			
		DEPTH	mm/in	198 / 7.8				198 / 7.8			
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	646 / 25.4				646 / 25.4			
		WIDTH	mm/in	840 / 33.1				840 / 33.1			
		DEPTH	mm/in	330 / 13				330 / 13			

MULTI-SPLIT AMSD-A SERIES WITH WALL MOUNTED-R22

HEAT PUMP MODEL		OUTDOOR UNIT		AMSD1020AR		AMSD1520AR		AMSD2020AR			
		INDOOR UNIT		AWM010GR		AWM020GR		AWM015GR			
NOMINAL COOLING CAPACITY		Btu/h		NOT AVAILABLE		11000		18000			
		W				3220		5280			
NOMINAL HEATING CAPACITY		Btu/h		NOT AVAILABLE		12000		19000			
		W				3520		5570			
COOLING ONLY MODEL		OUTDOOR UNIT		AMSD1020A		AMSD1520A		AMSD2020A			
		INDOOR UNIT		AWM010G		AWM020G		AWM015G			
NOMINAL CAPACITY		Btu/h		9500		18000		12700			
		W		2780		5280		3720			
POWER SOURCE		V/Ph/Hz		220 ~ 240 / 1 / 50		220 ~ 240 / 1 / 50		220 ~ 240 / 1 / 50			
INDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	260 / 10.2		306 / 12.0		260 / 10.2			
		WIDTH	mm/in	899 / 35.4		1062 / 41.8		899 / 35.4			
		DEPTH	mm/in	198 / 7.8		222 / 8.7		198 / 7.8			
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	632 / 24.9				632 / 24.9			
		WIDTH	mm/in	960 / 37.8				960 / 37.8			
		DEPTH	mm/in	437 / 17.2				437 / 17.2			

MULTI-SPLIT AMST-A SERIES WITH WALL MOUNTED-R22

HEAT PUMP MODEL		OUTDOOR UNIT		AMST101010AR			AMST101015AR			AMST101515AR			AMST151515AR		AMST101020AR	
		INDOOR UNIT		3 x AWM010GR	2 x AWM010GR	AWM015GR	AWM010GR	2 x AWM015GR	3 x AWM015GR	2 x AWM010GR	AWM0020GR	NOT AVAILABLE				
NOMINAL COOLING CAPACITY		Btu/h		3 x 9000	2 x 9000	12000	9000	2 x 12000	3 x 12000							
		W		3 x 2640	2 x 2640	3520	2640	2 x 3520	3 x 3520							
NOMINAL HEATING CAPACITY		Btu/h		3 x 9000	2 x 9000	11000	9000	2 x 11000	3 x 11000							
		W		3 x 2640	2 x 2640	3220	2640	2 x 3220	3 x 3220							
COOLING ONLY MODEL		OUTDOOR UNIT		AMST101010A			AMST101015A			AMST101515A			AMST151515A		AMST101020A	
		INDOOR UNIT		3 x AWM010G	2 x AWM010G	AWM015G	AWM010G	2 x AWM015G	3 x AWM015G	2 x AWM010G	AWM0020G					
NOMINAL CAPACITY		Btu/h		3 x 9000	2 x 9000	12700	9500	2 x 12700	3 x 12700	2 x 9000	18000					
		W		3 x 2640	2 x 2640	3720	2780	2 x 3720	3 x 3720	2 x 2640	5280					
POWER SOURCE		V/Ph/Hz		220 ~ 240 / 1 / 50			220 ~ 240 / 1 / 50			220 ~ 240 / 1 / 50			220 ~ 240 / 1 / 50			
INDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	260 / 10.2			260 / 10.2			260 / 10.2		306 / 12.0				
		WIDTH	mm/in	899 / 35.4			899 / 35.4			899 / 35.4		1062 / 41.8				
		DEPTH	mm/in	198 / 7.8			198 / 7.8			198 / 7.8		222 / 8.7				
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	631.7 / 24.9			631.7 / 24.9			631.7 / 24.9						
		WIDTH	mm/in	960.0 / 37.8			960.0 / 37.8			960.0 / 37.8						
		DEPTH	mm/in	437.0 / 17.2			437.0 / 17.2			437.0 / 17.2						

MULTI-SPLIT AMST-A SERIES WITH WALL MOUNTED-R22

COOLING ONLY MODEL		OUTDOOR UNIT		AMST101025A			AMST101525A			AMST151525A		
		INDOOR UNIT		2 x AWM010G	AWM025G	AWM010G	AWM015G	AWM025G	2 x AWM015G	AWM025G		
NOMINAL CAPACITY		Btu/h		2 x 9000	23000	9500	12000	23000	12000	23000		
		W		2 x 2640	6740	2780	3520	6740	3520	6740		
POWER SOURCE		V/Ph/Hz		220 ~ 240 / 1 / 50			220 ~ 240 / 1 / 50			220 ~ 240 / 1 / 50		
INDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	260 / 10.2	306 / 12.0	260 / 10.2		306 / 12.0	260 / 10.2		306 / 12.0	
		WIDTH	mm/in	899 / 35.4	1062 / 41.8	899 / 35.4		1062 / 41.8	899 / 35.4		1062 / 41.8	
		DEPTH	mm/in	198 / 7.8	222 / 8.7	198 / 7.8		222 / 8.7	198 / 7.8		222 / 8.7	
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	850 / 33.46			850 / 33.46			850 / 33.46		
		WIDTH	mm/in	1030 / 40.55			1030 / 40.55			1030 / 40.55		
		DEPTH	mm/in	400 / 15.75			400 / 15.75			400 / 15.75		

MULTISPLIT AMSD-A SERIES WITH CEILING CASSETTE

COOLING ONLY MODEL		OUTDOOR UNIT		AMSD1010A		AMSD1015A			AMSD1515A		
		INDOOR UNIT		ACK010C	ACK010C	ACK010C		ACK015C	ACK015C	ACK015C	
NOMINAL COOLING CAPACITY		Btu/h	9500		9500		12700		12700		
		W	2780		2780		3720		3720		
POWER SOURCE		V/Ph/Hz	220 ~ 240 / 1 / 50		220 ~ 240 / 1 / 50		220 ~ 240 / 1 / 50		220 ~ 240 / 1 / 50		
INDOOR UNIT	DIMENSION ()-PANEL	HEIGHT	mm/in	250 (295) / 9.8 (11.6)		250 (295) / 9.8 (11.6)		250 (295) / 9.8 (11.6)		250 (295) / 9.8 (11.6)	
		WIDTH	mm/in	570 (640) / 22.4 (25.2)		570 (640) / 22.4 (25.2)		570 (640) / 22.4 (25.2)		570 (640) / 22.4 (25.2)	
		DEPTH	mm/in	570 (640) / 22.4 (25.2)		570 (640) / 22.4 (25.2)		570 (640) / 22.4 (25.2)		570 (640) / 22.4 (25.2)	
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	646 / 25.4		646 / 25.4		646 / 25.4		646 / 25.4	
		WIDTH	mm/in	840 / 33.1		840 / 33.1		840 / 33.1		840 / 33.1	
		DEPTH	mm/in	330 / 13		330 / 13		330 / 13		330 / 13	

MULTISPLIT AMSD-A SERIES WITH CEILING CASSETTE

COOLING ONLY MODEL		OUTDOOR UNIT		AMSD1020A		AMSD1520A			AMSD2020A		
		INDOOR UNIT		ACK010C	ACK020C	ACK015C		ACK020C	ACK020C	ACK020C	
NOMINAL COOLING CAPACITY		Btu/h	9500		18000		12700		18000		
		W	2780		5275		3720		5280		
POWER SOURCE		V/Ph/Hz	220 - 240 / 1 / 50		220 - 240 / 1 / 50		220 - 240 / 1 / 50		220 - 240 / 1 / 50		
INDOOR UNIT	DIMENSION ()-PANEL	HEIGHT	mm/in	250 (295) / 9.8 (11.6)		250 (295) / 9.8 (11.6)		250 (295) / 9.8 (11.6)		250 (295) / 9.8 (11.6)	
		WIDTH	mm/in	570 (640) / 22.4 (25.2)		570 (640) / 22.4 (25.2)		570 (640) / 22.4 (25.2)		570 (640) / 22.4 (25.2)	
		DEPTH	mm/in	570 (640) / 22.4 (25.2)		570 (640) / 22.4 (25.2)		570 (640) / 22.4 (25.2)		570 (640) / 22.4 (25.2)	
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	632 / 24.9		632 / 24.9		632 / 24.9		632 / 24.9	
		WIDTH	mm/in	960 / 37.8		960 / 37.8		960 / 37.8		960 / 37.8	
		DEPTH	mm/in	437 / 17.2		437 / 17.2		437 / 17.2		437 / 17.2	

MULTISPLIT AMST-A SERIES WITH CEILING CASSETTE

COOLING ONLY MODEL		OUTDOOR UNIT		AMST101010A	AMST101015A		AMST101515A		AMST151515A	AMST101020A			
		INDOOR UNIT		3 x ACK010C	2 x ACK010C	ACK015C	ACK010C	2 x ACK015C	3 x ACK015C	2 x ACK010C	ACK020C		
NOMINAL COOLING CAPACITY		Btu/h	3 x 9500		2 x 9500		12700		9500		2 x 12700		
		W	3 x 2785		2 x 2785		3721		2780		2 x 3720		
POWER SOURCE		V/Ph/Hz	220 ~ 240 / 1 / 50		220 ~ 240 / 1 / 50		220 ~ 240 / 1 / 50		220 ~ 240 / 1 / 50		220 ~ 240 / 1 / 50		
INDOOR UNIT	DIMENSION ()-PANEL	HEIGHT	mm/in	250 (295) / 9.8 (11.6)		250 (295) / 9.8 (11.6)		250 (295) / 9.8 (11.6)		250 (295) / 9.8 (11.6)		250 (295) / 9.8 (11.6)	
		WIDTH	mm/in	570 (640) / 22.4 (25.2)		570 (640) / 22.4 (25.2)		570 (640) / 22.4 (25.2)		570 (640) / 22.4 (25.2)		570 (640) / 22.4 (25.2)	
		DEPTH	mm/in	570 (640) / 22.4 (25.2)		570 (640) / 22.4 (25.2)		570 (640) / 22.4 (25.2)		570 (640) / 22.4 (25.2)		570 (640) / 22.4 (25.2)	
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	631.7 / 24.9		631.7 / 24.9		631.7 / 24.9		631.7 / 24.9		631.7 / 24.9	
		WIDTH	mm/in	960 / 37.8		960 / 37.8		960 / 37.8		960 / 37.8		960 / 37.8	
		DEPTH	mm/in	437 / 17.2		437 / 17.2		437 / 17.2		437 / 17.2		437 / 17.2	

MULTISPLIT AMST-A SERIES WITH CEILING CASSETTE

COOLING ONLY MODEL		OUTDOOR UNIT		AMST101025A		AMST101525A			AMST151525A		
		INDOOR UNIT		2 x ACK010C	ACK025A	ACK010C	ACK015C	ACK025A	2 x ACK015C	ACK025A	
NOMINAL COOLING CAPACITY		Btu/h	2 x 9500		23000		9500		12000		
		W	2 x 2780		6740		2780		3520		
POWER SOURCE		V/Ph/Hz	220 ~ 240 / 1 / 50		220 ~ 240 / 1 / 50		220 ~ 240 / 1 / 50		220 ~ 240 / 1 / 50		
INDOOR UNIT	DIMENSION ()-PANEL	HEIGHT	mm/in	250 (295) / 9.8 (11.6)		335 (363) / 13.2 (14.3)		250 (295) / 9.8 (11.6)		250 (295) / 9.8 (11.6)	
		WIDTH	mm/in	570 (640) / 22.4 (25.2)		820 (930) / 32.2 (36.6)		570 (640) / 22.4 (25.2)		570 (640) / 22.4 (25.2)	
		DEPTH	mm/in	570 (640) / 22.4 (25.2)		820 (930) / 32.2 (36.6)		570 (640) / 22.4 (25.2)		570 (640) / 22.4 (25.2)	
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	850 / 33.46		850 / 33.46		850 / 33.46		850 / 33.46	
		WIDTH	mm/in	1030 / 40.5		1030 / 40.5		1030 / 40.5		1030 / 40.5	
		DEPTH	mm/in	400 / 15.75		400 / 15.75		400 / 15.75		400 / 15.75	

MULTISPLIT AMSD-A SERIES WITH CEILING CONCEALED

COOLING ONLY MODEL		OUTDOOR UNIT		AMSD1010A		AMSD1015A			AMSD1515A		
		INDOOR UNIT		ACC010C	ACC010C	ACC010C		ACC015C	ACC015C	ACC015C	
NOMINAL COOLING CAPACITY		Btu/h	9500		9500		12700		12700		
		W	2780		2780		3720		3720		
POWER SOURCE		V/Ph/Hz		220 - 240 / 1 / 50		220 - 240 / 1 / 50		220 - 240 / 1 / 50		220 - 240 / 1 / 50	
INDOOR UNIT	DIMENSION	HEIGHT	mm/in	261/10.28		261/10.28		261/10.28		261/10.28	
		WIDTH	mm/in	765/30.15		765/30.15		905/35.63		905/35.63	
		DEPTH	mm/in	411/16.18		411/16.18		411/16.18		411/16.18	
OUTDOOR UNIT	DIMENSION	HEIGHT	mm/in	646 / 25.4		646 / 25.4		646 / 25.4		646 / 25.4	
		WIDTH	mm/in	840 / 33.1		840 / 33.1		840 / 33.1		840 / 33.1	
		DEPTH	mm/in	330 / 13		330 / 13		330 / 13		330 / 13	

MULTISPLIT AMSD-A SERIES WITH CEILING CONCEALED

COOLING ONLY MODEL		OUTDOOR UNIT		AMSD2020A		AMSD1520A			AMSD2020A		
		INDOOR UNIT		ACC010C	ACC020C	ACC015C		ACC020C	ACC020C	ACC020C	
NOMINAL COOLING CAPACITY		Btu/h	9500		18000		12700		18000		
		W	2780		5280		3720		5280		
POWER SOURCE		V/Ph/Hz		220 - 240 / 1 / 50		220 - 240 / 1 / 50		220 - 240 / 1 / 50		220 - 240 / 1 / 50	
INDOOR UNIT	DIMENSION	HEIGHT	mm/in	261/10.28		261/10.28		261/10.28		261/10.28	
		WIDTH	mm/in	765/30.15		1065/41.93		905/35.63		1065/41.93	
		DEPTH	mm/in	411/16.18		411/16.18		411/16.18		411/16.18	
OUTDOOR UNIT	DIMENSION	HEIGHT	mm/in	632 / 24.9		632 / 24.9		632 / 24.9		632 / 24.9	
		WIDTH	mm/in	960 / 37.8		960 / 37.8		960 / 37.8		960 / 37.8	
		DEPTH	mm/in	437 / 17.2		437 / 17.2		437 / 17.2		437 / 17.2	

MULTISPLIT AMST-A SERIES WITH CEILING CONCEALED

COOLING ONLY MODEL		OUTDOOR UNIT		AMST101010A	AMST101015A		AMST101515A		AMST151515A	AMST101020A			
		INDOOR UNIT		3 x ACC010C	2 x ACC010C	ACC015C	ACC010C	2 x ACC015C	3 x ACC015C	2 x ACC010C	ACC020C		
NOMINAL COOLING CAPACITY		Btu/h	3 x 9500		2 x 9500		12700		9500		2 x 12700		
		W	3 x 2780		2 x 2780		3720		2780		2 x 3720		
POWER SOURCE		V/Ph/Hz		220 - 240 / 1 / 50		220 - 240 / 1 / 50		220 - 240 / 1 / 50		220 - 240 / 1 / 50			
INDOOR UNIT	DIMENSION	HEIGHT	mm/in	261/10.28		261/10.28		261/10.28		261/10.28		261/10.28	
		WIDTH	mm/in	765/30.12		765/30.12		905/35.63		765/30.12		1065/41.93	
		DEPTH	mm/in	411/16.18		411/16.18		411/16.18		411/16.18		411/16.18	
OUTDOOR UNIT	DIMENSION	HEIGHT	mm/in	631.7 / 24.9		631.7 / 24.9		631.7 / 24.9		631.7 / 24.9		631.7 / 24.9	
		WIDTH	mm/in	960 / 37.8		960 / 37.8		960 / 37.8		960 / 37.8		960 / 37.8	
		DEPTH	mm/in	437 / 17.2		437 / 17.2		437 / 17.2		437 / 17.2		437 / 17.2	

MULTISPLIT AMST-A SERIES WITH CEILING CONCEALED

COOLING ONLY MODEL		OUTDOOR UNIT		AMST101025A		AMST101525A			AMST151525A		
		INDOOR UNIT		ACC010C x 2	ACC025C	ACC010C	ACC015C	ACC025C	ACC015C x 2	ACC025C	
NOMINAL COOLING CAPACITY		Btu/h	2 x 9500		23000		9500		12000		
		W	2 x 2780		6740		2780		3520		6740
POWER SOURCE		V/Ph/Hz		220 - 240 / 1 / 50		220 - 240 / 1 / 50		220 - 240 / 1 / 50		220 - 240 / 1 / 50	
INDOOR UNIT	DIMENSION	HEIGHT	mm/in	261/10.28		261/10.28		261/10.28		261/10.28	
		WIDTH	mm/in	765/30.12		1200/47.24		765/30.12		905/35.63	
		DEPTH	mm/in	411/16.18		411/16.18		411/16.18		411/16.18	
OUTDOOR UNIT	DIMENSION	HEIGHT	mm/in	850 / 33.46		850 / 33.46		850 / 33.46		850 / 33.46	
		WIDTH	mm/in	1030 / 40.55		1030 / 40.55		1030 / 40.55		1030 / 40.55	
		DEPTH	mm/in	400 / 15.75		400 / 15.75		400 / 15.75		400 / 15.75	

MULTI-SPLIT A4MSD-A SERIES WITH WALL MOUNTED - R407C

HEATPUMP MODEL		OUTDOOR UNIT		A4MSD1010AR		A4MSD1015AR		A4MSD1515AR		
		INDOOR UNIT		2 x AWM 010GR		AWM 010GR		AWM 015GR		
NOMINAL COOLING CAPACITY		Btu/h		2 x 9000		9000		10500		2 x 10500
		W		2 x 2640		2640		3080		2 x 3080
NOMINAL HEATING CAPACITY		Btu/h		2 x 9000		9000		11500		2 x 11500
		W		2 x 2640		2640		3370		2 x 3370
COOLING ONLY MODEL		OUTDOOR UNIT		A4MSD1010A		A4MSD1015A		A4MSD1515A		
		INDOOR UNIT		2 x AWM 010G		AWM 010G		AWM 015G		
NOMINAL CAPACITY		Btu/h		2 x 9000		9000		12000		2 x 12000
		W		2 x 2640		2640		3520		2 x 3520
POWER SOURCE		V/Ph/Hz		220 ~ 240 / 1 / 50		220 ~ 240 / 1 / 50		220 ~ 240 / 1 / 50		
INDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	260 / 10.2		260 / 10.2		260 / 10.2		
		WIDTH	mm/in	899 / 35.4		899 / 35.4		899 / 35.4		
		DEPTH	mm/in	198 / 7.8		198 / 7.8		198 / 7.8		
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	646 / 25.4		646 / 25.4		646 / 25.4		
		WIDTH	mm/in	840 / 33.1		840 / 33.1		840 / 33.1		
		DEPTH	mm/in	330 / 13		330 / 13		330 / 13		

MULTI-SPLIT A4MST-A SERIES WITH WALL MOUNTED - R407C

HEATPUMP MODEL		OUTDOOR UNIT		A4MST101010AR		A4MST101015AR		A4MST101515AR		A4MST151515AR		
		INDOOR UNIT		3 x AWM 010GR		2 x AWM 010GR		AWM 015GR		AWM 010GR		
NOMINAL COOLING CAPACITY		Btu/h		3 x 9000		2 x 9000		12000		9000		2 x 12000
		W		3 x 2640		2 x 2640		3520		2640		2 x 3520
NOMINAL HEATING CAPACITY		Btu/h		3 x 9000		2 x 9000		11000		9000		2 x 11000
		W		3 x 2640		2 x 2640		3220		2640		2 x 3220
COOLING ONLY MODEL		OUTDOOR UNIT		A4MST101010A		A4MST101015A		A4MST101515A		A4MST151515A		
		INDOOR UNIT		3 x AWM 010G		2 x AWM 010G		AWM 015G		AWM 010G		
NOMINAL CAPACITY		Btu/h		3 x 9000		2 x 9000		12000		9000		2 x 12000
		W		3 x 2640		2 x 2640		3520		2640		2 x 3520
POWER SOURCE		V/Ph/Hz		220 ~ 240 / 1 / 50		220 ~ 240 / 1 / 50		220 ~ 240 / 1 / 50		220 ~ 240 / 1 / 50		
INDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	260 / 10.2		260 / 10.2		260 / 10.2		260 / 10.2		
		WIDTH	mm/in	899 / 35.4		899 / 35.4		899 / 35.4		899 / 35.4		
		DEPTH	mm/in	198 / 7.8		198 / 7.8		198 / 7.8		198 / 7.8		
OUTDOOR UNIT	UNIT DIMENSION	HEIGHT	mm/in	631.7 / 24.9		631.7 / 24.9		631.7 / 24.9		631.7 / 24.9		
		WIDTH	mm/in	960.0 / 37.8		960.0 / 37.8		960.0 / 37.8		960.0 / 37.8		
		DEPTH	mm/in	437.0 / 17.2		437.0 / 17.2		437.0 / 17.2		437.0 / 17.2		